



# APPEARANCE 2000®

## Urethane Fortified Floor Finish

### PRODUCT DESCRIPTION:

Appearance 2000® offers the latest in floor finish technology for the ultra high-speed floor care market. This high solids urethane fortified floor finish in combination with an ultra high speed burnishing program delivers the best looking floor at the lowest possible overall cost.

### FEATURES:

#### Urethane Fortified:

Enhances gloss and improves resistance to scratching and scuffing.

#### Durable/Cost Efficient:

Extends time between buffing cycles, resulting in reduced maintenance costs.

#### Produces "Wet Look":

Used in conjunction with a high speed buffer or burnisher produces gloss, "wet look" floor. Does not powder. Long wearing.

#### UL Approved for Slip Resistance:

Provides a safe, slip resistant surface.

### PRODUCT SPECIFICATIONS:

pH	8.6 ± 0.2
Appearance	Off White Emulsion
Fragrance	Acrylic
Freezing Point	About 32°F
% Solids	20.0%
Boiling Point	212°F
Solubility in Water	Dispersible
Flash Point	None
Coverage	1800 to 2200 sq. ft. per gallon
(may vary due to differences in porosity of the surface)	


### INGREDIENTS:

Water	7732-18-5
Ammonia	7664-41-7
Styrene Acrylic Polymer	25085-34-1
Polyurethan	9002-88-4
Diethylene Glycol Methyl Ether	111-77-3
Ethylene Copolymer	67892-91-5

### PRODUCT AVAILABILITY:

- 9641.....4/1 gal
- 9645.....2/2.5 gal
- 96455.....1/55 gal drum

### END-USE-RATING



0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Minimo	Minimo	Moderar	Grave	Drastico

DATA SHEET

FULLPRO  
FULLER PROFESSIONAL

# APPEARANCE 2000®

Urethane Fortified Floor Finish



**USE INFORMATION:** Appearance 2000® Floor Finish is recommended for use in spray buffing, high-speed buffing and especially high speed burnishing maintenance programs. This product is recommended for use on all resilient flooring, tile, terazzo, and clay tile. Not recommended for use on unsealed wood floors.

## INITIAL APPLICATION



CAUTION



1. REMOVE



2. APPLY



3. DRY



4. APPLY


## MAINTENANCE



1. DUST MOP



2. MOP



3. SPRAY BUFF

## DIRECTIONS FOR USE:

### INITIAL APPLICATION

1. **REMOVE** old sealer/finish using a Fullpro stripper and following label directions.
2. **APPLY** a thin coat of **Appearance 2000®** using a clean finish mop.
3. **DRY:** Allow 20-30 minutes drying time.
4. **APPLY** 4 coats for best results allowing for adequate drying time between each coat.

### MAINTENANCE

1. **Dust mop**, damp mop or sweep regularly. Use a neutral cleaner such as CONCUR™.
2. **Mop** on APPEARANCE® MAINTAINER and allow to dry.
3. **Burnish** using a natural or appropriate synthetic buffing pad.
4. **As needed**, thoroughly scrub, rinse and recoat worn areas with APPEARANCE 2000® to maintain the foundation or base.

### FIRST AID:

**If in eyes or on skin**, immediately flush with plenty of water. Get medical attention if irritation persists. **If swallowed**, get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

### HANDLING AND STORAGE:

**SUGGESTED STORAGE TEMPERATURE:** Store inside at 40-90°F. **SPECIAL HANDLING AND STORAGE:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool, dry, ventilated area. **Protect from freezing.** Thoroughly rinse empty containers.

**KEEP OUT OF REACH OF CHILDREN**

### PERSONAL PROTECTION:

**Respiratory Protection:** Not needed under normal conditions.

**Ventilation:** Use with adequate ventilation.

**Eye Protection:** Safety glasses are recommended.

**Protective Gloves:** Protective gloves are optional.

**Other Protective Clothing or Equipment:** Wear clothing as necessary to prevent skin contact.

### TRANSPORTATION INFORMATION:

**U.S. DOT - Proper Shipping Name:** Not regulated by DOT.

**Marine Pollutant:** No



CLEANING TECHNOLOGIES GROUP™

© FULLER BRUSH COMPANY® • 2007  
Great Bend, KS 67530 964TDS-0807

MSDS Retrieval  
Obtención de HDSM

www.cleaningtechnology.com  
800-848-4901

DATA SHEET  
FULLPRO  
FULLER PROFESSIONAL