



MOMENTUM™

Ultra Durable Floor Finish

PRODUCT DESCRIPTION:

Momentum™ is an advanced technology floor coating specially formulated with our exclusive APT™ Polymer System. Momentum™ will provide exceptional durability, repairability and a beautiful wet look gloss while reducing labor costs and burnishing frequencies up to 50%. Momentum™ allows facilities currently burnishing 5-7 times per week to drop back to 3-4 times per week when used according to directions with the recommended system components.

FEATURES:

Reduced Environmental Impact:

Because of reduced burnishing needed to maintain Momentum™, it reduces energy usage and helps provide a healthier, safer environment for employees and customers.

Easy to Apply:

Momentum™ has very little mop drag and can normally be recoated after 20 minutes depending on temperature/humidity.

Cost Reducing:

When used as directed with recommended system components, Momentum™ can reduce burnishing, labor and associated costs by up to 50% in high maintenance programs without sacrificing appearance.

Ultra Durable:

Momentum™ is extremely resistant to abrasions such as scratching, scuffing and heel marking. Momentum™ will not capture and embed soils, which results in less time to clean, less chemical to use and less overall cost to maintain while enjoying a high maintenance look.

PRODUCT SPECIFICATIONS:

pH (concentrate)	9.05 ± 0.45
Appearance	Off white emulsion
Fragrance	Acrylic
Freezing Point	About 32°F
% Solids	18.4 ± 0.4
Solubility in Water	Complete
Flash Point	None
Coverage	up to 3000 sq. ft. per gallon (may vary due to differences in porosity of the surface and application method used)

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.


INGREDIENTS:

Water	7732-18-5
NJ TSRN	100555-5009
Dipropylene glycol methyl ether	34590-94-8
Diethylene glycol ethyl ether	111-90-0
Tributoxyethyl phosphate	78-51-3

PRODUCT AVAILABILITY:

- 9685 2/2.5 gal

END-USE-RATING



0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Minimo	Minimo	Moderar	Grave	Drastico

DATA SHEET

FULLPRO
FULLER PROFESSIONAL

MOMENTUM™ Ultra Durable Floor Finish



Use Information: Momentum™ is part of a complete floor care system made up of Fullpro's Razor Stripper, Fullgard Sealer, Nushine UHS Combo Cleaner/Maintainer, Fuller Brush finish mops and Brillo floor pads. When used as directed this system will allow up to a 50% reduction of burnishing in high maintenance floor care programs while maintaining a wet look gloss. For use on vinyl composition, vinyl, asphalt, sealed concrete, terrazzo and sealed wood.

INITIAL APPLICATION



CAUTION



1. REMOVE



2. APPLY



20 minutes

3. DRY




4. APPLY



5. BURNISH


MAINTENANCE



1. DUST MOP



2. MOP



3. BURNISH

DIRECTIONS FOR USE:

INITIAL APPLICATION

1. **REMOVE** old sealer/finish using Fullpro Razor stripper and following label directions. Before coating an old or porous floor use 2 coats of Fullpro Fullgard to seal the floor.
2. **APPLY** a thin coat of Momentum using a clean Fuller Brush Finish Mop.
3. **DRY:** Allow 20 minutes drying time.
4. **APPLY** a total of 4-6 thin coats allowing adequate drying time between each coat.
5. **BURNISH:** Optional - following last coat after minimum 1 hour dry time.

MAINTENANCE

1. **DUST MOP** the floor several times daily. Remove gum, labels, and other attached soil deposits with a long-handled scraper or putty knife..
2. **DAMP MOP OR AUTOSCRUB** daily using Fullpro Nushine UHS Combo Cleaner/Maintainer and following the label directions.
3. **BURNISH** the floor 3-4 times per week with an ultra high speed machine (>2000 RPM) using a Brillo Natural Lite pad or equivalent. If the floor begins to look worn, a scrub & recoat after 6-8 weeks will decrease the need for frequent stripping.

FIRST AID:

If in eyes or on skin, immediately flush with plenty of water. Get medical attention if irritation persists. If swallowed, get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

HANDLING AND STORAGE:

SUGGESTED STORAGE TEMPERATURE: Store inside at 40-90°F. **SPECIAL HANDLING AND STORAGE:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool, dry, ventilated area. **Protect from freezing.** Thoroughly rinse empty containers.

KEEP OUT OF REACH OF CHILDREN

PERSONAL PROTECTION:

Respiratory Protection: Not needed under normal conditions.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety glasses are recommended.

Protective Gloves: Protective gloves are optional.

Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION INFORMATION:

U.S. DOT - Proper Shipping Name: Not regulated by DOT.

Marine Pollutant: No.

DATA SHEET

FULLPRO
FULLER PROFESSIONAL