T.E.T.® THESE = THOSE

NEUTRAL FLOOR CLEANER

USE DIRECTIONS: Set trigger sprayer to deliver a fine mist. Spray onto surface to be cleaned until evenly wet. Wipe off with a clean cloth until surface is dry. For additional directions see concentrate label.

Do not mix with any other products. For Industrial Use only. In emergency call Chemtrec 800-424-9300.

CAUTION: May cause eye and skin irritation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Consult original container for precautions and first aid for concentrate.

KEEP OUT OF REACH OF CHILDREN.

INGREDIENTS: Water (7732-18-5), Nonyl phenoxy poly (ethyleneoxy) ethanol (9016-45-9), Triethanolamine (102-71-6), EDTA (60-00-4), Fragrance (N/A).

TECH HOTLINE 800-810-4829
MSDS FAX RETRIEVAL 800-551-0101

FRANKLIN CLEANING TECHNOLOGY

© **FRANKLIN** Cleaning Technology® 2002
Great Bend, KS 67530
www.franklintechnology.com

Work Solution:

This bottle contains a work solution of T.E.T.® Neutral Floor Cleaner.

(F375418)

Disuelto para su uso:

Esta botella continene una solución de Trabajo de Limpiador Neutro de Piso de T.E.T.®.

(F375418)



0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Minimo	Minimo	Moderar	Grave	Drastico

DE LIMPIADOR NEUTRO DE PISO

INSTRUCCIONES PARA USARLO: Ajuste la pistola de rocío para que produzca una neblina densa. Rocíe la superficie a limpiar hasta que la misma se moje; sequela con una toalla limpia. Para instrucciones adicionales vea la etiqueta del concentrado.

No mezclarlo con otros productos. Para uso industrial exclusivamente. En caso de urgencia, llamar a Chemtrec 800-424-9300.

PRECAUCIÓN: Puede ocasionar irritación ocular y dérmica. Evitar el contacto con los ojos, la piel y la ropa. Lavarse meticulosamente después de la manipulación. Consultar en el recipiente original las precauciones a observar por concentrado.

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.

INGREDIENTES: Agua (7732-18-5), Nonifenoxipoli (etileneoxi) etanol (9016-45-9), Trietanolamina (102-71-6), EDTA (60-00-4), Fragancia (N/A).

LINEA DE TECNICA 800-810-4829
OBTENCION DE HDSM POR FAX 800-551-0101

F3754SEC-1102

2 2 2 2 2 2 2 2 2 2