



#8 Glass & Multi-Surface Cleaner

DATA
TECH
SHEET

PRODUCT DESCRIPTION:

A Green Certified, advanced formulation of special ingredients to dissolve greasy film, fingerprints and smears. Leaves glass and reflective surfaces smudge and streak free. Effectively cleans glass, mirrors, Plexiglas, acrylic, stainless steel, chrome, counter tops, tabletops and other reflective surfaces.

FEATURES:

User Friendly:

Fast drying formula, cuts through film and grime quickly. It leaves surfaces sparkling clean with no streaks or smears. Quick easy cleaning reduces labor.

Cost Effective:

Multi-surface cleaner recommended for use on glass, windows, mirrors, plastic, Plexiglas®, metal and other hard surfaces. Reduces the number of cleaning products required and simplifies training requirements.

PRODUCT SPECIFICATIONS:

| | |
|---------------------------|-------------------|
| pH (concentrate) | 6.8 ± 0.6 |
| Appearance | Clear Blue Liquid |
| Fragrance | None Added |
| Solubility in Water | Complete |
| Flash Point | > 200° F |

INGREDIENTS

| | |
|-------------------------------|-------------|
| Water | 7732-18-5 |
| NJ TRSN | 100555-5002 |
| Magnesium alkyl sulfate | 3097-08-3 |
| NJ TRSN | 100555-5003 |



Recognized for Safer Chemistry
www.epa.gov/dfc

| DILUTIONS | HEALTH | FLAMMABILITY | REACTIVITY |
|--------------------------------|-------------|----------------|-------------|
| CONCENTRATE CONCENTRAR | NFPA 1 HMIS | NFPA 0 HMIS | NFPA 0 HMIS |
| (1:128 RATIO) (1:128 RAZÓN) | NFPA 0 HMIS | NFPA 0 HMIS | NFPA 0 HMIS |
| PROPORCIÓN | SALUD | INFLAMABILIDAD | REACTIVIDAD |

| 0 | 1 | 2 | 3 | 4 |
|---------|--------|----------|---------|----------|
| Minimal | Slight | Moderate | Serious | Severe |
| Mínimo | Mínimo | Moderar | Grave | Drástico |

#8 Glass & Multi-Surface Cleaner Lightning Blend System

DIRECTIONS

USE INFORMATION:

Dilute the product at 1:128 (one ounce per gallon of **COLD** water). The Lightning Blend proportioner is preset to deliver this ratio of mixed solution to a spray bottle. Use the diluted product as directed.



UNIT DIRECTIONS:

1. **PLACE** discharge tube into a spray bottle.
2. **TURN ON** the **COLD** water supply.
3. **PUSH** in the button to dispense the solution.
4. **RELEASE** the button to stop the flow of the solution.

DIRECTIONS FOR USE:

1. **SPRAY** surfaces from 6 to 12 inches away, using a fine mist. Spray on sparingly.
2. **WIPE** dry immediately with a clean, dry cloth or paper towel.
3. **SQUEEGEE** may also be used effectively in addition to a dry cloth or paper towel.

FIRST AID:

If in eyes, flush immediately with cold water. Remove contact lenses. Continue flushing for 15 minutes holding eyelids apart. Get medical attention. **If swallowed**, promptly drink large quantities of water. Get medical attention. **NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.**

HANDLING AND STORAGE:

SUGGESTED STORAGE TEMPERATURE: Store inside at 40-90°F. **SPECIAL HANDLING AND STORAGE:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool, dry, ventilated area. Protect from freezing. Thoroughly rinse empty containers. **KEEP OUT OF REACH OF CHILDREN.**

PERSONAL PROTECTION:

Respiratory Protection: Not needed in normal use.
Ventilation: Use with adequate ventilation.
Eye Protection: Safety glasses are optional.
Protective Gloves: Protective gloves are optional.
Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION INFORMATION:

U.S. DOT - Proper Shipping Name: Not restricted by DOT.
Marine Pollutant: No

MSDS RETRIEVAL
Read MSDS before using this product

800-848-4901

www.franklintechnology.com

OBTENCIÓN DE HDSM
Leer la HDSM antes de utilizar este producto

FOR CHEMICAL EMERGENCY,
SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT
CALL CHEMTREC DAY OR NIGHT
800-424-9300

PARA EMERGENCIAS QUÍMICA DERRAMES,
ESCAPES, FUEGO, EXPOSICIÓN O ACCIDENTE
LLAMAR DE DÍA O DE NOCHE A CHEMTREC

TECH HOTLINE
800-810-4829
LINEA DE TÉCNICA