

Out-Strip®

AUTOSCRUB STRIPPER

DATA TECH SHEET

PRODUCT DESCRIPTION:

Out-Strip® is an extremely powerful floor finish and wax remover that is formulated primarily for use with an automatic scrubber. Stripping the floor with an automatic scrubber saves labor. It can also be used as a conventional stripper with a mop and bucket. Safe on most resilient and non-resilient floors including mineral surfaces, terrazzo, concrete, vinyl, vinyl composition, asphalt, rubber, terrazzo, brick and quarry tile. Do not use on linoleum or tile that are in poor condition.

FEATURES:

Fast Acting:

Quickly penetrates the finish minimizing the abrasion needed to remove the finish.

Non-ammoniated:

No ammonia odor. Reduces complaints while stripping the floor.

Efficient Finish Removal:

The automatic scrubber easily picks up the emulsified finish. Only one piece of equipment is needed to apply and pick-up the stripper solution.

PRODUCT SPECIFICATIONS:

pH	12.9 ± 0.1
Appearance	Light Yellow Liquid
Fragrance	Light Solvent
Freezing Point	About 32°F
Solubility in Water	Complete
Flash Point	None

INGREDIENTS:

Water	7732-18-5
Ethylene glycol phenyl ether	122-99-6
Monoethanolamine	141-43-5
2-Butoxyethanol	111-76-2
Isopropyl alcohol	67-63-0

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE CONCENTRAR	NFPA 3 HMIS	NFPA 0 HMIS	NFPA 0 HMIS
(1:8 RATIO) (1:8 RAZÓN)	NFPA 2 HMIS	NFPA 0 HMIS	NFPA 0 HMIS
(1:4 RATIO) (1:4 RAZÓN)	NFPA 1 HMIS	NFPA 0 HMIS	NFPA 0 HMIS
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico

ECOLOGICAL INFORMATION:

- Biodegradable Surfactants
- Contains No Phosphorus

Out-Strip® AUTOSCRUB STRIPPER

DIRECTIONS

USE INFORMATION


Before stripping always dust mop the floor and remove gum, labels and other attached soil deposits with a long handled scraper or putty knife.

AUTOSCRUB STRIPPING



CAUTION 1. DILUTE 2. APPLY 3. SCRUB/REMOVE

ROTARY MACHINE STRIPPING



CAUTION 1. DILUTE 2. APPLY 3. SCRUB 4. REMOVE 5. RINSE

AUTOSCRUB STRIPPING

1. **DILUTE** at 16 oz. per gallon (1:8 ratio) or up to 32 oz. per gallon (1:4 ratio) of cool water.
2. **APPLY** diluted solution of **Out-Strip®** using a black pad under low pressure. Do not pick up solution and do not let dry.
3. **SCRUB:** Repeat scrubbing action on second pass without applying solution. Scrub areas that are not accessible with a doodlebug or long handled scraper. **REMOVE** and pick-up emulsified finish on third and final pass. Inspect and make sure the floor is free of stripper solution before applying the finish. **REPEAT** steps two and three if any finish remains on the floor. A rinse may be required for dilutions stronger than 1:4.

ROTARY MACHINE STRIPPING

1. **DILUTE** at 16 oz. per gallon (1:8 ratio) or up to 32 oz. per gallon (1:4 ratio) of cool water.
2. **APPLY** the diluted solution liberally with a mop on a small section.
3. **SCRUB** the floor with a black or brown pad.
4. **REMOVE** the remaining solution off the floor using a mop or wet vacuum.
5. **RINSE** the floor with clean water using a mop or wet vacuum.

FIRST AID:

If in eyes or on skin, immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. **If inhaled,** remove to fresh air. Get medical attention. **If swallowed,** get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

HANDLING AND STORAGE:

SUGGESTED STORAGE TEMPERATURE: Store inside at 40-90°F. **SPECIAL HANDLING AND STORAGE:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool, dry, ventilated area. **Protect from freezing.** Thoroughly rinse empty containers. **KEEP OUT OF REACH OF CHILDREN.**

PERSONAL PROTECTION:

Respiratory Protection: Not needed under normal conditions.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety glasses are required.

Protective Gloves: Safety gloves are required.

Other Protective Clothing or Equipment:

Wear clothing as necessary to prevent skin contact.



TRANSPORTATION INFORMATION:

U.S. DOT - Proper Shipping Name: Not regulated by DOT.

Marine Pollutant: No.

MSDS FAX RETRIEVAL
Read MSDS before using this product

800-551-0101

OBTENCIÓN DE HDSM POR FAX
Leer la HDSM antes de utilizar este producto

FOR CHEMICAL EMERGENCY,
SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT
CALL CHEMTREC DAY OR NIGHT

800-424-9300

PARA EMERGENCIAS QUÍMICA DERRAMES,
ESCAPES, FUEGO, EXPOSICIÓN O ACCIDENTE
LLAMAR DE DÍA O DE NOCHE A CHEMTREC

TECH HOTLINE
800-810-4829
LINEA DE TÉCNICA