



CLEARINSE® PLUS Foaming Degreaser

USE DIRECTIONS: Dilute product into spray bottle following label directions. Apply to surface to be cleaned. Allow to set for 3-5 minutes agitating if necessary. Rinse with hot potable water. For additional directions see concentrate label.

Do not mix with any other products. For industrial use only. In emergency call Chemtrec 800-424-9300.

WARNING: Causes eye and skin irritation. May cause respiratory tract irritation. Avoid contact with eyes, skin and clothing. Avoid breathing vapors. Wash thoroughly after handling. Consult original container for precautions and first aid for concentrate.

KEEP OUT OF REACH OF CHILDREN.

INGREDIENTS: Water (7732-18-5), Dipropylene glycol methyl ether (34590-94-8), Potassium dodecylbenzene sulfonate (27177-77-1), Sodium xylene sulfonate (1300-72-7), Alkyl ether sulfate, sodium salt (73665-22-2).

TECH HOTLINE 800-810-4829
MSDS RETRIEVAL 800-848-4901

© Cleaning Technologies Group® 2005
Great Bend, KS 67530
www.trumix.biz

Work Solution:

This bottle contains a work solution of Trumix Clearinse® Plus Foaming Degreaser (F5941)

Disuelto para su uso:

Esta botella contiene una solución de Trumix Clearinse® Plus Espumante y Desgrasador (F5941)

CLEARINSE® PLUS Espumante y Desgrasador

INSTRUCCIONES PARA USARLO: Diluya el producto en la botella rociadora. Aplique a la superficie que va a ser limpiada. Déjelo de 3 a 5 minutos agitando si es necesario. Enjuague con agua potable caliente. Para instrucciones adicionales vea la etiqueta del concentrado.


No mezclarlo con otros productos. Para uso industrial exclusivamente. En caso de urgencia, llamar a Chemtrec 800-424-9300.

ADVERTENCIA: Causes irritación de la piel y de los ojos. Puede causar irritación de las vías respiratorias. Evitar el contacto con los ojos. Evitar respirar el vapor. Lavarse meticulosamente después de la manipulación. Consultar en el recipiente original las precauciones a observar por concentrado.

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.

INGREDIENTES: Agua (7732-18-5), Éter dipropileno glico metílico (34590-94-8), Sulfonato de potasio dodecilbenzeno (27177-77-1), Sulfonato de xileno de sodio (1300-72-7), Sulfato éter aquirlico, sal de sodio (73665-22-2).

LINEA DE TECNICA 800-810-4829
OBTENCION DE HDSM 800-848-4901



0 1 2 3 4

Minimal	Slight	Moderate	Serious	Severe
Minimo	Minimo	Moderar	Grave	Drastico

F5941SEC-0405PS

41

41

41

41

41

41

41

41

41

41